

Glass frosters

- › Featuring the award winning low maintenance +stayclear condenser
- › Frosted glasses ready in minutes
- › Technologically advanced system prevents condensation on glass doors
- › A range of styles to suit all bars
- › Easy to service design

› **Gamko** glass frosters

For the perfect serve.



Icy cold glasses

Our glass frosters feature the award winning +stayclear condenser, making them not only stylish to look at but reliable and high performing. With a range of finishes and options available, they will seamlessly fit into your bar.

Gamko glass frosters not only ensure quality, but also efficiency. If you store beverages at room temperature, but need to serve them chilled, a Gamko glass froster is the solution. No longer will you have to pre-chill your glasses with crushed ice in advance of cocktail making.



GF/100LSCS



GF/100LGCS



GF/100LG



GF/100LS

Accessories

Item number

Wire mesh shelf (486 x 330mm)	004010425
Shelf support (4 per shelf)	013010001

General characteristics glass frosters

- > +stayclear condenser as standard
- > Energy efficient R600a hydrocarbon refrigerant as standard
- > Plug and go! No need for a separate cooling unit
- > Extremely efficient cooling system
- > Electronic thermostat with digital display
- > Automatic defrost
- > Condensation prevention system on all glass door models
- > LED light on all models
- > Adjustable front feet
- > Replaceable door seals
- > Can be built in or standalone



MODEL	DOOR TYPE	STORAGE CAPACITY (PINT GLASSES)	REFRIGERANT	TEMPERATURE	EXTERIOR FINISH	DIMENSIONS W x D x H*
GF/100RG	right hinged glass door	50 glasses (ø88mm)	R600a	-14°C / -10°C	anthracite	600 x 508 x 840/880 mm
GF/100LG	left hinged glass door	50 glasses (ø88mm)	R600a	-14°C / -10°C	anthracite	600 x 508 x 840/880 mm
GF/100RGCS	right hinged glass door	50 glasses (ø88mm)	R600a	-14°C / -10°C	stainless steel	600 x 508 x 840/880 mm
GF/100LGCS	left hinged glass door	50 glasses (ø88mm)	R600a	-14°C / -10°C	stainless steel	600 x 508 x 840/880 mm
GF/100RS	right hinged solid door	50 glasses (ø88mm)	R600a	-14°C / -10°C	anthracite	600 x 508 x 840/880 mm
GF/100LS	left hinged solid door	50 glasses (ø88mm)	R600a	-14°C / -10°C	anthracite	600 x 508 x 840/880 mm
GF/100RSCS	right hinged solid door	50 glasses (ø88mm)	R600a	-14°C / -10°C	stainless steel	600 x 508 x 840/880 mm
GF/100LSCS	left hinged solid door	50 glasses (ø88mm)	R600a	-14°C / -10°C	stainless steel	600 x 508 x 840/880 mm

① Conditions: Te = -25°C | Tc = +45°C | ambient temperature = +25°C

* Depth of the cabinet excludes handgrip. During installation: add 40 mm to the overall depth (in conjunction with the appliance's plug) and add 10 mm to the total width.

No rights can be derived from the information as shown in this brochure. Content, technical features and prices subject to change. 2/2019